


ACCEPTED VENDORS:
MOTION & FLOW CONTROL PRODUCTS
834 S.E FRONTAGE RD.
FORT COLLINS, CO 80524

MANUFACTURER:
PARKER-HANNIFIN
WWW.PARKER.COM

MATERIAL:
PTFE TUBE
304 STAINLESS STEEL BRAID REINFORCEMENT

MEETS STANDARDS:
SAE 100R14A: FOR HIGH TEMPERATURE FLUIDS

REVISION HISTORY					
DATE	REV	DESCRIPTION	AUTHOR	CHECKED BY	APPROVED
9/9/19	A	INITIAL RELEASE	DT	LS	JA



PTFE HOSE				
-#	MFG. P/N	NOMINAL I.D. (in.)	MAX O.D. (in.)	MAX WORKING PRESSURE (psi)
1	919-10	1/2	0.66	2500
2	919-8	13/32	0.56	2000
3	919-6	5/16	0.46	1500

PTFE HOSE

NOTE:
This drawing defines the overall geometry and performance specifications of the part/assembly, and constitutes the acceptance criteria thereof. Only the item(s) described in this document procured from the vendor and/or manufacturer listed hereon are approved for use. A substitute item shall not be used without prior approval. Conformance of hardware to these requirements is acceptable in lieu of vendor and/or manufacturer documentation.

~CONFIDENTIAL INFORMATION~
THE INFORMATION AND DATA CONTAINED HEREIN IS PROPRIETARY AND IS SUBMITTED IN CONFIDENCE, AND SHALL NOT BE DISCLOSED, USED OR DUPLICATED FOR ANY PURPOSE WHATSOEVER WITHOUT THE PRIOR WRITTEN PERMISSION OF PARAVION TECHNOLOGY, INC.

PROTO

Paravion® Technology Inc.		TITLE PTFE HOSE		DRAWING NUMBER ES45022	
DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTED: .X = ±.1 .XX = ±.05 .XXX = ±.010 ANGLES = ± 1°		DRAWN BY DT	CHK'D BY LS	APRVD. BY JA	DATE 9/9/19
THREADS: INTERNAL: CLASS 2B EXTERNAL: CLASS 2A		DO NOT SCALE DRAWING		REV A	ECO
3RD ANGLE PROJECTION		© 2019 PARAVION TECH. INC. PARAVION IS A TRADEMARK OF PARAVION TECHNOLOGY INC.		SHEET 1 OF 1	